

DUCTILE IRON FITTINGS



Information - Characteristics

ALL FLANGED TEE

CAST IRON GJL-250

BITUMINUS PAINT ALTERNATIVELY EPOXY COATING

THICKNESS 150-250mm

FLANGE PUNCHING IN 1092-2 PN 10-16

DN	dn	WEIGHT		DN	dn	WEIGHT	
50	50	12	✓	300	50	80	✓
65	50	12	✓		65	80	✓
	65	12	✓		80	77	✓
80	50	16	✓		100	70	✓
	65	16	✓		125	85	✓
	80	17	✓		150	97	✓
100	50	21	✓		200	105	✓
	65	21	✓		250	136	✓
	80	21	✓		300	132	✓
	100	21	✓	350	50	138	✓
125	50	24	✓		65	138	✓
	65	24	✓		80	98	✓
	80	26	✓		100	118	✓
	100	27	✓		125	130	✓
	125	28	✓		150	97	✓
150	50	32	✓		200	132	✓
	65	32	✓		250	157	✓
	80	34	✓		300	150	✓
	100	35	✓		350	190	✓
	125	36	✓	400	50	155	✓
	150	39	✓		65	155	✓
200	50	41	✓		80	122	✓
	65	41	✓		100	122	✓
	80	43	✓		125	166	✓
	100	44	✓		150	138	✓
	125	47	✓		200	161	✓
	150	56	✓		250	198	✓
	200	64	✓		300	200	✓
250	50	60	✓		350	250	✓
	65	60	✓		400	275	✓
	80	60	✓	500	100	241	✓
	100	62	✓		125	243	✓
	125	72	✓		150	243	✓
	150	75	✓		200	245	✓
	200	90	✓		250	258	✓
	250	96	✓		300	264	✓
					350	268	✓
					400	276	✓
					500	301	✓
				600	600	434	✓